

▶ Liquid Tight Conduit - Heavy Duty

Standard: UL 360

Material: Steel, with Heavy PVC Coated

Application: can be used in both dry and wet locations where it would be impractical to install EMT or other non-flexible conduit



EVT#	Trade Size	Metric Designator	Inside Diameter		Outside Diameter		Min. Bend Radius(mm)	Meters / Coil
			Min(mm)	Max(mm)	Min(mm)	Max(mm)		
LTC11	3/8"	12	12.29	12.80	17.50	18.00	50	100
LTC12	1/2"	16	15.80	16.31	20.80	21.30	80	100
LTC13	3/4"	21	20.83	21.34	25.20	26.70	105	50
LTC14	1"	27	26.44	27.08	32.80	33.40	165	50
LTC15	1-1/4"	35	35.05	35.81	41.40	42.20	200	25
LTC16	1-1/2"	41	40.01	40.64	47.40	48.30	225	25
LTC17	2"	53	51.31	51.94	59.40	60.30	280	20
LTC18	2-1/2"	63	62.99	63.63	72.10	73.00	370	20
LTC19	3"	78	77.98	78.74	87.90	88.90	440	10
LTC21	4"	103	101.60	102.62	113.30	114.30	600	10

▶ Liquid Tight Conduit - Light Duty

Standard: UL 360

Material: Steel, with Light PVC Coated

Application: can be used in both dry and wet locations where it would be impractical to install EMT or other non-flexible conduit



EVT#	Trade Size	Metric Designator	Inside Diameter		Outside Diameter		Min. Bend Radius(mm)	Meters / Coil
			Min(mm)	Max(mm)	Min(mm)	Max(mm)		
PFC01	3/8"	12	12.29	12.80	16.70	17.20	35	100
PFC02	1/2"	16	15.80	16.31	20.20	20.70	65	100
PFC03	3/4"	21	20.83	21.34	25.50	26.10	75	50
PFC04	1"	27	26.44	27.08	31.60	32.20	100	50
PFC05	1-1/4"	35	35.05	35.81	40.80	41.50	125	25
PFC06	1-1/2"	41	40.01	40.64	46.60	47.20	150	25
PFC07	2"	53	51.31	51.94	58.10	58.70	175	20
PFC08	2-1/2"	63	62.99	63.63	71.80	72.40	200	20
PFC09	3"	78	77.98	78.74	87.20	87.90	225	10
PFC10	4"	103	101.60	102.62	111.20	112.30	275	10